



CABLE-4-20mA

4 to 20 mA Input

Cable for connecting a sensor with a 4-20mA output to a HOBO U12, UX120, or ZW series external-channel data logger.

Supported Measurements:

4-20mA



Key Advantages:

- 18.5 inches in length
- Can be plugged directly into the external input jacks of U12, UX120, or ZW series loggers to expand the range of measurement options and applications.

CABLE-4-20mA Specifications

Measurement range: 0 to 20.1 mA

Accuracy with U12: ± 0.02 mA $\pm 2.5\%$ of absolute current

Accuracy with ZW: ± 0.015 mA $\pm 2.0\%$ of absolute current

Accuracy with UX120-006M: ± 0.001 mA $\pm 0.2\%$ of absolute current

Resolution with U12 and ZW: 0.03% of full scale

Resolution with UX120-006M: 0.002% of full scale

Cable length: 47 cm (18.5 inches)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532