



HOBO® H22-001 Data Logger

H22 Energy Data Logger

Monitor energy and industrial equipment with this 15-channel data logger (Part # H22-001). With multiple channels, energy and facility managers can quickly and easily detect and address a variety of issues relating to HVAC, machinery, and other systems. The HOBO H22-001 Energy Data Logger is modular and more economic than its alternatives because a toolbox full of data loggers is not necessary.

Deploy this product with a variety of pre-defined plug-and-play smart sensors to create a robust monitoring system. Compatible with HOBOWare® software, researchers can conduct effective data analysis in minutes.



Supported Measurements:

4-20mA, AC Current, AC Voltage, Air Velocity, Amp Hour (Ah), Carbon Dioxide, Compressed Air Flow, DC Current, DC Voltage, Differential Pressure, Gauge Pressure, Kilowatt Hours (kWh), Kilowatts (kW), Power Factor (PF), Pulse Input, Relative Humidity, Temperature, Volatile Organic Comp., Volt-Amp Reactive, Volt-Amp Reactive hour, Volt-Amps (VA), Water Flow, Watt Hours (Wh) and Watts (W)

Key Advantages:

- Onset's most flexible data logger records up to 15 channels of over a dozen measurements
- Provides 12v excitation for third-party sensors
- Pre-configured smart sensors get you started fast
- Signal conditioning modules retain configurations until you change them, providing plug-and-play convenience for commonly used sensors
- Flexible power options include battery operation for AC power adapter

HOBO H22-001 Data Logger Specifications

Operating range:

-20° to 50°C (-4° to 122°F) with alkaline batteries

-40° to 60°C (-40° to 140°F) with lithium batteries

Sensor inputs: Three FlexSmart multi-channel modules and up to 6 Smart Sensors (which may have multiple parameters/channels)

Sensor connectors: Six RJ-12 Smart Sensor jacks plus 3 FlexSmart module slots

Communication: RS-232 via 3.5 mm serial port or/and 9-pin D-Sub connector

Dimensions: 15.6 cm x 8.4 cm x 4.6 cm (6.13" x 3.31" x 1.81")

Weight: 435 g (15.23 oz) with batteries 238 g (8.33 oz) without batteries

Memory: 512K nonvolatile flash data storage

Memory modes: Stop when full; wrap when full

Operational indicators: Six indicators provide logging and sensor network status

Logging interval: One second to 18 hours, user-specified interval (2-second minimum for two-channel S-FS-TRMSA operation)

Sensor excitation: 12 V DC at 200 mA total, with user-programmable warmup time on a per-channel basis

Battery life: One year typical use (up to 75 mA excitation with 10-minute or longer logging Interval and 1-second warmup time)

Battery type: Eight standard AA alkaline batteries included (for operating conditions -20°C/-4°F to 50°C/122°F); optional AA lithium batteries available for operating conditions of -40° to 60°C (-40° to 140°F).

External power: Supports optional 13.6 V DC regulated AC Wall Adapter Connector. Internal batteries may remain installed. Alternatively, an automotive battery or 9-12 V DC regulated Wall Adapter may be used, but it is recommended to remove the internal batteries since they will discharge to the level of the external supply.

Time accuracy: 0 to 2 seconds for the first data point and ±5 seconds per week at 25°C (77°F)

Logging mode: Immediate, timed delay, or trigger (button-push) start options; supports sampling intervals for some sensors

Data communication: Current readings while logging; read out while logging; read out when stopped

This product meets CE specification EN61326 criterion C for ESD, criterion C for Radiated Immunity, criterion B for Fast Transient, criterion A for Conducted Immunity, and criterion A for Power Frequency Magnetic Fields. To minimize measurement errors due to ambient RF, use the shortest possible probe sensor cable length.

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

► Email sales@onsetcomp.com

► Call 1-508-759-9500

► In U.S. toll free 1-800-564-4377

► Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

► Contact Product Support www.onsetcomp.com/support/contact

► Call 1-508-759-9500

► In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532