



HOBO® ZW-ROUTER

data router

The HOBO® data router routes data from networked HOBO data nodes to ensure that the data is transmitted back to the receiver.



Key Advantages:

- Simple, cost-effective solution for transmitting data from HOBO data nodes that are too far away from the receiver or whose signal is blocked by an obstruction or interferences
- Automatically determines the best path to deliver node data back to the receiver
- Improves the reliability and redundancy of data node networks

HOBO ZW-ROUTER Specifications

Power: AC Adapter.

Range: Approx. 100 m (300 ft.) depending on obstructions or interference

Weight: 138 g (4.87 oz.) w/ batteries

Size: 96.5 x 108 x 28 mm (3.8 x 4.25 x 1.1 in.)

Operating Range

Temp: -20 to 50°C (-4 to 122°F) when battery powered, -20 to 70°C (-4 to 158°F) when line powered.

RH: 5%-95% non-condensing

Measurement range: N/A

Accuracy: N/A

Resolution: N/A

Response time: N/A

Radio power: 1.6 mW (2 dBm)

Wireless data standard: IEEE 802.15.4 2.4 GHz band

CE - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

► Email sales@onsetcomp.com

► Call 1-508-759-9500

► In U.S. toll free 1-800-564-4377

► Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

► Contact Product Support www.onsetcomp.com/support/contact

► Call 1-508-759-9500

► In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532